

Diaphragm pressure gauge for the process industry

Model 432.56, high overload safety up to 100 bar

Model 432.36, safety version, high overload safety up to 400 bar

WIKA data sheet PM 04.07



for further approvals
see page 3

Applications

- For measuring points with increased overload
- For gaseous, liquid and aggressive media, also in aggressive ambience
- With the open connecting flange option also for contaminated and viscous media
- Process industry: Chemical, petrochemical, power plants, mining, on-/offshore, environmental technology, machine building and general plant construction

Special features

- High overload safety, optionally 40, 100 or 400 bar, due to metallic diaphragm cushion, without liquid-filled measuring cell
- Wide choice of special materials
- Compatible with switch contacts
- All stainless steel construction
- Scale ranges from 0 ... 16 mbar

Description

Design

EN 837-3

Nominal size in mm

100, 160

Accuracy class

1.6

Scale ranges ¹⁾

0 ... 16 mbar to 0 ... 250 mbar

0 ... 400 mbar to 0 ... 40 bar

or all other equivalent vacuum or combined pressure and vacuum ranges

Pressure limitation

Steady: Full scale value

Fluctuating: 0.9 x full scale value



Diaphragm pressure gauge, model 432.56

Overload safety ¹⁾

- 40 bar
- 100 bar
- 400 bar (only for scale ranges $\geq 0 \dots 400 \text{ mbar}^2$)

Permissible temperature

Ambient: -20 ... +60 °C

Medium: $\leq 100 \text{ °C}$

Temperature effect

When the temperature of the measuring system deviates from the reference temperature (+20 °C): $\leq \pm 0.8 \text{ \%}/10 \text{ K}$ of full scale value

Ingress protection per IEC/EN 60529

- IP54
- IP65 for models with liquid filling

¹⁾ Depending on scale range and overload safety, different flange \varnothing apply. Dimensions, see page 4.

²⁾ 400 bar overload safety for scale ranges < 400 mbar on request

Standard version

Process connection with lower measuring flange

Stainless steel, G ½ B (male)

Pressure element

≤ 0.25 bar: Stainless steel

> 0.25 bar: NiCr-alloy (Inconel)

Pressure chamber sealing

FPM/FKM

Movement

Stainless steel

Dial

Aluminium, white, black lettering

Pointer

- Adjustable pointer, aluminium, black
- Standard pointer, aluminium, black (for models with liquid filling)

Case

Stainless steel, instruments with liquid filling with compensating valve to vent case

Model 432.56: With blow-out device

Model 432.36: Safety version with solid baffle wall (Solid-front) and blow-out back

Upper measuring flange and flange connecting screws

Stainless steel

Window

Laminated safety glass

Bezel ring

Bayonet ring, stainless steel


Options

- Other process connection
- Sealings (model 910.17, see data sheet AC 09.08)
- Liquid filling (models 433.56, 433.36, ingress protection IP65)
- Vacuum safe to -1 bar
- Max. medium temperature +200 °C
- Permissible ambient temperature -40 ... +60 °C (silicone oil filling)
- Higher indication accuracy, class 1.0
- Open connecting flanges per DIN/ASME, DN 15 to DN 80 (preferred nominal widths DN 25 and 50 or DN 1" and 2" per data sheet IN 00.10)
- Wetted parts made of special materials, high overload safety up to 10 bar (flange Ø 160 mm) or 40 bar (flange Ø 100 mm): PTFE (models 452.56, 452.36), Hastelloy, Monel, nickel, tantalum, titanium (accuracy class 2.5)
- Additional wall bracket for model 432.36, high overload safety up to 400 bar¹⁾
- Diaphragm pressure gauge with switch contacts, see data sheet PV 24.07
- Diaphragm pressure gauge with electrical output signal, see model PGT43HP, data sheet PV 14.07

1) Recommendation with vibration load > 0.5 g

Dimensions in mm

Standard version



NS	Scale ranges	Overload safety	Dimensions in mm									Weight in kg
	in bar	up to ... bar	d	a	b	D ₁	D ₂	e	G	h ±2	SW	
100	≤ 0.25	40	160	15.5	49.5	101	99	17.5	G ½ B	135	27	3.4
		100	160	15.5	49.5	101	99	17.5	G ½ B	143	22	6.3
	> 0.25	40	100	15.5	49.5	101	99	17.5	G ½ B	135	27	1.7
		100	100	15.5	49.5	101	99	17.5	G ½ B	135	27	1.8
160	≤ 0.25	40	160	15.5	49.5	161	159	17.5	G ½ B	165	27	4.0
		100	160	15.5	49.5	161	159	17.5	G ½ B	173	22	6.9
	> 0.25	40	100	15.5	49.5	161	159	17.5	G ½ B	165	27	2.2
		100	100	15.5	49.5	161	159	17.5	G ½ B	165	27	2.3
		400	128	23.5	65	161	160	17.5	G ½ B	199	22	6.9

Process connection per EN 837-3 / 7.3

© 03/2008 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.
 The specifications given in this document represent the state of engineering at the time of publishing.
 We reserve the right to make modifications to the specifications and materials.